## **Evidence of Performance**

Air permeability, Watertightness, Resistance to wind load

Material: Aluminium profiles with thermal break

Test Report No. 11-003702-PR01

(PB-A01-02-en-01)

Client SARAY Aluminium

Product Tilt and turn window

Designation System designation: SI 58 Sistem

1,200 mm x 1,500 mm

Performance-relevant

product details

Overall dimensions (WxH)

Special features

ROSENHEIM

Basis

EN 14351-1:2006+A1:2010

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12046-1:2003-11 EN 12211:2000-06 EN 14609:2004-06 Correspond/s to the national

standard/s (e.g. DIN EN)

Representation



Instructions for use

The results obtained can be used by the manufacturer as the basis for the manufacturer ITT test report summary. Observe the specifications set out by the applicable product standard.

## Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented, in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The ift-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 21 pages.

## Results

Air permeability according to EN 12207:1999-11



Class 4

Watertightness according to EN 12208:1999-11



Class 8A

Resistance to wind load according to EN 12210:1999-11/AC:2002-08



Class C4 / B4

ift Rosenheim 16.03.2012

Jörn Peter Lass, Dipl.-Ing. (FH) Head of Testing Department **Building Components** 

Robert Kolacny, Dipl.-Ing. Operating Product Officer **Building Components** 

